



Features & Description

- Certified to 10/100/1000Mbps transmission speed.
- All feature four pairs (7X32AWG) RJ45 connectors, and PVC jacket.
- Constructed of enhanced performance stranded UTP and FTP Cable.

Physical Specifications

- Fire-retardant (FR-PVC)* cable construction
- Cable type : 4 pair stranded UTP
- 7 x 32 AWG conductor gauge
- Hood Assembly: Plastic, with molded/booted hood
- Connector: Rj45
- Insertion life cycle: 1,000 cycles (min)
- Plug retention force:30.1b (min.)

Electrical Characteristics

- Impedance : 100 ±15
- Resistance : 45 /1,000 ft. (304.8 m)
- Mutual Capacitance : 17nf/1,000 ft. (Maximum).
- DC Resistance : Max. 28.6 /100 ft. at 20°C
- Operating temperature: -20 °C to ± 75 °C

Standards

- EIA/TIA568.B2
- ISO 11801 2nd. Version
- EN 50173-1

Applications

- 10 BaseT, 100BaseTX, 1000BaseT
- 4-16Mbit Token Ring
- 622-155Mbit ATM
- ISDN
- Analog Voice

* LSFROH & Non-Plenum also available

Ordering Information:

Part No:

PC-C5E-U-0,5
PC-C5E-U-1
PC-C5E-U-3
PC-C5E-U-5
PC-C5E-F-0,5
PC-C5E-F-1
PC-C5E-F-3
PC-C5E-F-5

Description:

XPcable CAT5E 0,5m UTP Patch Cord
XPcable CAT5E 1m UTP Patch Cord
XPcable CAT5E 3m UTP Patch Cord
XPcable CAT5E 5m UTP Patch Cord
XPcable CAT5E 0,5m FTP Patch Cord
XPcable CAT5E 1m FTP Patch Cord
XPcable CAT5E 3m FTP Patch Cord
XPcable CAT5E 5m FTP Patch Cord



ELECTRONICS CO., LTD.

RM A206, 11FL, No. 51 Hengyang Road, Taipei 100, Taiwan, R.O.C.

www.xpcable.com